

## Technical Data Sheet

Date of Issue 06/06/2016

Rev. 00\_06/06/2016

# 4040 Multiple Surfaces Double Sided Tape



### Product Description

A premier double-sided cloth based tape suitable for retaining carpet and vinyl flooring and perfect for critical applications as: metal onto wood, metal onto metal etc.

Being highly versatile, the product can be used on most surfaces and applications requiring a strong permanent bond.

### Features

- Highly Conformable
- High Strength
- Hand Tearable
- High Adhesion

### Main Applications

- Retaining carpet and vinyl flooring

### Technical Data

|                        | Units | Std. Values |
|------------------------|-------|-------------|
| Total Thickness        | µm    | 250         |
| MD tensile strength    | µm    | 17          |
| MD elongation at break | %     | 4           |
| Peel Adhesion          | N/cm  | 22          |
| Rolling Ball           | cm    | 3           |
| Shear Strength STD     | h     | 15          |
| Service Temperature    | °C    | -10 +50     |

### Carrier

Synthetic Cloth

### Liner

Yellow 70 mic Silicon Paper

### Type of adhesive

Hot Melt Synthetic Rubber

### Available colour



Yellow

### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.