

## Technical Data Sheet

Date of Issue 06/06/2016

Rev. 00\_06/06/2016

# 750

## Double Sided Acrylic UPVC Tape



### Product Description

750 is a double sided product especially suitable for assembling and mounting operations where excellent resistance to plastificer migration is needed. It has also a very good conformability to rough or uneven surfaces.

Its applications vary from furniture trim and roller blind assembly to retention of plastic cable trunking.

### Features

- Excellent Adhesion Features
- High Strength
- Quality release paper for ease of removal
- Good Conformability
- Good Ageing Characteristics

### Main Applications

- Assembling and mounting
- Furniture and Roller blind assembly
- Mounting of signs and point of sale displays

### Technical Data

	Units	Std. Values
Total Thickness	µm	210
Backing Thickness	µm	50
MD tensile strength	Kg/mm <sup>2</sup>	8
MD elongation at break	%	180
TD tensile strength	Kg/mm <sup>2</sup>	4
TD elongation at break	%	120
Peel Adhesion	N/cm	9

### Carrier

Unplasticized PVC

### Liner

90GM/  
M2 Honey Glassline Paper

### Type of adhesive

Solvent Acrylic

### Available colour



Transparent

### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.