

**Technical Data Sheet**

Date of Issue 11/10/2016

Rev. 00\_11/10/2017

# Green Bubble Wrap

## Fragile Protection

### Self Adhesive

### Protective Cushion

**Product Description**

Green Bubble Wrap is a transparent, self-adhesive LDPE protection film, coated with a low tack clean removable water based acrylic adhesive system. This product is especially developed for the protection of polished and glossy surfaces, such as glass, stainless steel, varnished and anodized surfaces during repair, decoration and refurbishment operations.

Envisaged surfaces include ceramic floor & wall tiles, sanitary ware, sinks, baths and shower floor areas. Surfaces to be protected should be dry, free from, dust, oil solvents or other chemicals.

**Features**

- Low Tack Adhesion
- UV Resistant
- Clean Removal

**Main Applications**

- Protection Delicate Surfaces during refurbishment

**Technical Data**

	Units	Std. Values
Tensile strength	N/cm	0.2-0.5
Peel Adhesion	N/cm	0.2-0.5
Service Temperature	°C	15-40

**Backing material**

32 Micron LD Polythene Film  
+ Bubble Film

**Type of adhesive**

Acrylic Emulsion

**Available colour**

Green

**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

**Storage and Shelf Life**

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.