

**Technical Data Sheet**

Date of Issue 06/06/2016

Rev. 00\_06/06/2016

# 4101

## High Tack Double Sided

**Product Description**

A higher adhesive coat weight, hotmelt, plasticiser free, clear polypropylene double sided tape. Can be used in splicing applications and in areas of uneven or irregular surface finish.

Also used for carpet fixing and associated general purpose application.

**Features**

- High Coat Weight
- Plasticiser Free
- High Tack Adhesive
- High Strength

**Main Applications**

- Splicing Applications
- Carpet Fixing

**Technical Data**

	Units	Std. Values
Total Thickness	µm	155
MD tensile strength	N/cm	21
MD elongation at break	%	490
Adhesion to steel plate	N/cm	20
Service Temperature	°C	-10 +50

**Carrier**

Bi-Axially Oriented  
Clear Polypropylene

**Liner**

Brown 80 mic Silicon Paper

**Type of adhesive**

Hot Melt Synthetic Rubber

**Available colour**

Brown

**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

**Storage and Shelf Life**

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.