

**Technical Data Sheet**

Date of Issue 11/10/2016

Rev. 01\_13/07/2018

# 6009

## Entry Level Masking Tape

**Product Description**

Entry Level, medium/high adhesion masking tape characterized by a thin crepe paper backing and a synthetic rubber resin solvent free adhesive. Suitable for indoor light duty applications, for non-critical masking and painting operations, and for general bundling, holding, splicing, and labeling.

It is recommended to use at room temperature.

**Features**

- Thin paper for general masking operations
- Excellent quality price ratio
- Good contact on multiple surfaces
- Good paint anchorage

**Main Applications**

- Light duty painting operations (no UV exposure recommended)
- Non - critical bundling, splicing and holding
- General labeling and marking activities

**Technical Data**

	<b>Metric</b>	<b>Imperial Units</b>	<b>Test Method</b>
Total weight*	70 g/m <sup>2</sup>	70 g/m <sup>2</sup>	ISO 536
Total thickness*	92 µm	3.6 mils	AFERA 5006/PSTC 133
MD tensile strength*	30 N/cm	17.1 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	3.5 N/cm	32 oz/in	AFERA 5001/PSTC 101

**Backing material**

Saturated crepe paper

**Type of adhesive**

Synthetic rubber resin - solvent free

\*Typical value

**Available colour**

White    Yellow

**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

**Storage and Shelf Life**

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.